



LED DISPLAYS:ELD-1201C/D SERIES

ELECTRICAL AND OPTICAL CHARACTERISTICS (Ta=25°C)

Part No.	Emittd Color	PeakWave Length	Epoxy Color	Surface Color	Common Electrode	$\Delta\lambda$ (nm)	Pd (mW)	If (mA)	Peak (mA)	Vf(V)		IV(mcd)	
										Min	Max	Min	Max
ELD-1201CS	Red	620-630	White	Black	Cathode	10	35	20	60	1.8	2.0	82	92
ELD-1201CO	Orange	600-610	White	Black	Cathode	10	35	20	60	1.8	2.0	85	95
ELD-1201CY	Yellow	585-595	White	Black	Cathode	10	35	20	60	1.8	2.0	88	98
ELD-1201CG	Olivine	565-575	White	Black	Cathode	10	35	20	60	1.8	2.0	10	20
ELD-1201CGG	Emerald	515-525	White	Black	Cathode	10	55	20	60	2.6	2.8	215	225
ELD-1201CB	Blue	460-470	White	Black	Cathode	10	55	20	60	2.6	2.8	15	25
ELD-1201CW	White	-	-	Black	Cathode	-	55	20	60	2.6	2.8	-	-
ELD-1201DS	Red	620-630	White	Black	Anode	10	35	20	60	1.8	2.0	82	92
ELD-1201DO	Orange	600-610	White	Black	Anode	10	35	20	60	1.8	2.0	85	95
ELD-1201DY	Yellow	585-595	White	Black	Anode	10	35	20	60	1.8	2.0	88	98
ELD-1201DG	Olivine	565-575	White	Black	Anode	10	35	20	60	1.8	2.0	10	20
ELD-1201DGG	Emerald	515-525	White	Black	Anode	10	55	20	60	2.6	2.8	215	225
ELD-1201DB	Blue	460-470	White	Black	Anode	10	55	20	60	2.6	2.8	15	25
ELD-1201DW	White	-	-	Black	Anode	-	55	20	60	2.6	2.8	-	-

ABSOLUTE MAXIMUM RATINGS (Ta=25°C)

ReverseVoltage	ReverseCurrent (VR=5V)	OperatingTemperature Range	StorageTemperature Range	Lead Soldering Temperature
5V	20 μ A	-20°C~+80°C	-30°C~+80°C	255 °C For 3 seconds

PACKAGE DIMENSION (Unit: millimeters, Tolerance : ± 0.25 mm)

