



LED DISPLAYS: ELD-5269A/B SERIES

ELECTRICAL AND OPTICAL CHARACTERISTICS (Ta=25°C)

Part No.	Emittd Color	PeakWave Length	Epoxy Color	Surface Color	Common Electrode	$\Delta\lambda$ (nm)	Pd (mW)	If (mA)	Peak (mA)	Vf(V)		IV(mcd)	
										Min	Max	Min	Max
ELD-5269AS	Red	620-630	White	Black	Cathode	10	35	20	60	1.8	2.0	82	92
ELD-5269AO	Orange	600-610	White	Black	Cathode	10	35	20	60	1.8	2.0	85	95
ELD-5269AY	Yellow	585-595	White	Black	Cathode	10	35	20	60	1.8	2.0	88	98
ELD-5269AG	Olivine	565-575	White	Black	Cathode	10	35	20	60	1.8	2.0	10	20
ELD-5269AGG	Emerald	515-525	White	Black	Cathode	10	55	20	60	2.6	2.8	215	225
ELD-5269AB	Blue	460-470	White	Black	Cathode	10	55	20	60	2.6	2.8	15	25
ELD-5269AW	White	-	-	Black	Cathode	-	55	20	60	2.6	2.8	-	-
ELD-5269BS	Red	620-630	White	Black	Anode	10	35	20	60	1.8	2.0	82	92
ELD-5269BO	Orange	600-610	White	Black	Anode	10	35	20	60	1.8	2.0	85	95
ELD-5269BY	Yellow	585-595	White	Black	Anode	10	35	20	60	1.8	2.0	88	98
ELD-5269BG	Olivine	565-575	White	Black	Anode	10	35	20	60	1.8	2.0	10	20
ELD-5269BGG	Emerald	515-525	White	Black	Anode	10	55	20	60	2.6	2.8	215	225
ELD-5269BB	Blue	460-470	White	Black	Anode	10	55	20	60	2.6	2.8	15	25
ELD-5269BW	White	-	-	Black	Anode	-	55	20	60	2.6	2.8	-	-

ABSOLUTE MAXIMUM RATINGS (Ta=25°C)

Reverse Voltage	Reverse Current (VR=5V)	Operating Temperature Range	Storage Temperature Range	Lead Soldering Temperature
5V	20 μ A	-20°C ~ +80°C	-30°C ~ +80°C	255 °C For 3 seconds

PACKAGE DIMENSION (Unit: millimeters, Tolerance : ± 0.25 mm)

